








H280T

Technical data




 Max Lifting Capacity	 Engine Power	 Travel Speed	 Hydraulic Flow	 Max Lifting Height
1500 kg	34.3 kw	25 km/h	60 l/min	4 m



Technical data	H280T	
Engine model	YANMAR 4TNV88-BIGE	Kubota V2403-M-DI-E3B-CSL1T
Fuel type	Diesel	
Cylinders	4	
Displacement cc	2190	2434
Emission standards	EU Stage V	China Off-Road GB4
Max engine output kW	18.5@1500rpm	36.5@2600 rpm
Max engine torque Nm	141@1500rpm	158.6@1600rpm
Cooling system	Water	
Operating voltage V	12	
Battery Ah	70	
Operating weight kg	3500	
Tipping load ,max kg	1700	
Lifting capacity,max kg	1500	
Operator's cab	Cabin	
Travel speed km/h	0~25	
Steering angle °	45	
Turn radius inside/outside mm	1600/3430	
Standard tires	10.0/75-15.3	
Fuel tank capacity l	40	
Hydraulic oil tank capacity l	50	
Working hydraulic flow l/min	60	
Working hydraulic pressure bar	160	
Transmission type	Hydrostatic	

H280T

Dimensions/mm



Tires size	Height	Width
10.0/75-15.3	2395	1198
31/15.5-15	2400	1450

Products will continue to be optimized, so the technical data on this page may not be updated in real time.
 For more information at: www.heracles.eu
 Or contact us (contact information is on the back cover).